


armor

1400 SERIES DOOR CLOSER

FEATURES

- (1) Aluminium alloy die casting body. Modernize style, sliding dress cover.
- (2) Suitable for hollow steel, and wood doors with any kind of frame, reversible hand installed.
- (3) Provide whole series from size 2 to size 4 for wider range application.
- (4) According to installed dimension be able to select desirable opening angle.
- (5) universal application for STANDARD, TOP JAMB and PARALLEL arm installation
- (6) Precise two speed adjusting valve for control door closing smoothly.




SELECTION CHART

SIZE No .	STANDARD / TOP JAMB INSTALLATION				DOOR WEIGHT (Ret) lbs
	Interior door width (mm)	Exterior door width(mm)		Minimum (Kgf.m)	
		Swing out	Swing in		
1402	900	800	700	1.0	25~45
1403	950	900	800	1.7	40~65
1404	1050	950	900	2.7	60~85

ADJUSTMENT

- (1) Individual two speed adjusting valves for adjust both closing speed from 180 °~15 ° and 15 °~0 °.
- (2) Speed adjusting valves turned clockwise for slow down the closing speed, turned counterclockwise for speed up the closing speed.
- (3) The closing speed adjust range from 180 ° to 15 ° and latching speed adjust from 15 ° to 0 ° (refer to FIG. A).
- (4) Choose either of slide arm or cam hold-open arm (option), it may hold the door in any of your set-up point within 75 ° to 180 °.



HENG KUO CO., LTD. – (TAIWAN)
KUNSHAN HENG KUO MACHINERY CO., LTD

TAIWAN PLANT : No136, Ren De 5, Ta-Shi, Tao Yuan Hsien,
Taiwan R.O.C.
TEL : 886-3-380-2101 FAX : 886-3-380-2123
CHINA PLANT : No.388 Lu Cnen Road kun Shan City CHINA
TEL : 86-512-861-86625 FAX : 86-512-575-70392