

armor

70 SERIES DOOR CLOSER



FEATURES

- Hydraulic door closer
- Size 2 to size 5 with different body sizes
- The hardened steel rack and pinion mechanism is housed in the alloy aluminum body
- Reversible for both left and right handed doors
- Universal applications for standard, top jamb, or parallel arm installation (Optional parallel bracket)
- Swtable for both metal and wooden doors
- Adjustable closing speed from 180° ~15° by turning the adjusting valve 1
- Adjustable latching speed from 15° ~0° by turning the adjusting valve 2
- Standard in BACK CHECK.






SELECTION CHART

SIZE No .	STANDARD / TOP JAMB INSTALLATION				PARALLEL INSTALLATION				DOOR WEIGHT (Ret) lbs
	Interior door width (mm)	Exterior door width(mm)		Minimum Lbf.	Interior door width (mm)	Exterior door width(mm)		Minimum Lbf.	
		Swing out	Swing in			Swing out	Swing in		
72	900	800	700	5	800	700	600	3	44~88
73	950	900	800	6	900	800	700	5	88~132
74	1050	950	900	8	950	900	800	6	132~176
75	1200	1050	950	11	1050	950	900	8	176~220



	mm						
	A	B	C	D	E	F	G
72	160	305	187	73.4	9.5	12.7	22.6
73	151	305	208	73.4	9	12.7	22.6
74	140	305	230	76.5	9	13	22.6
75	140	305	230	76.5	9	13	22.6




HENG KUO CO., LTD. – (TAIWAN)
KUNSHAN HENG KUO MACHINERY CO., LTD

TAIWAN PLANT : No136, Ren De 5, Ta-Shi, Tao Yuan Hsien, Taiwan R.O.C.
TEL : 886-3-380-2101 FAX : 886-3-380-2123
CHINA PLANT : No.388 Lu Chen Road kun Shan City CHINA
TEL : 86-512-861-86625 FAX : 86-512-575-70392

Installation instructions


Standard Installation
(Closer mounted on door on pull side)



Same dimensions apply to Left Hand Doors.
Measurements B & C start from the edge of the door.

Closer size	A	FOR OPENING TO 120 °		FOR OPENING TO 180 °	
		B	C	B	C
2	7 ³ / ₈ " (187mm)	6 ⁵ / ₁₆ " (160mm)	12" (305mm)	4 ⁷ / ₈ " (124mm)	10" (254mm)
3	8 ³ / ₁₆ " (208mm)	5 ¹⁵ / ₁₆ " (151mm)	12" (305mm)	4 ¹ / ₂ " (114mm)	10" (254mm)
4&5	9 ¹ / ₁₆ " (230mm)	5 ¹ / ₂ " (140mm)	12" (305mm)	4 ¹ / ₁₆ " (103mm)	10" (254mm)


Top Jamb Installation
(Closer mounted on top jamb on push side of door)



Same dimensions apply to Right Hand Doors.
Measurements B & C start from the edge of the door.

Closer size	A	FOR OPENING TO 120 °		FOR OPENING TO 180 °	
		B	C	B	C
2	7 ³ / ₈ " (187mm)	6 ⁷ / ₁₆ " (164mm)	11 ³ / ₄ " (298mm)	4 ¹ / ₄ " (108mm)	8 ³ / ₄ " (222mm)
3	8 ³ / ₁₆ " (208mm)	6 ¹ / ₁₆ " (154mm)	11 ³ / ₄ " (298mm)	3 ⁷ / ₈ " (98mm)	8 ³ / ₄ " (222mm)
4&5	9 ¹ / ₁₆ " (230mm)	5 ⁵ / ₈ " (143mm)	11 ³ / ₄ " (298mm)	3 ⁷ / ₁₆ " (87mm)	8 ³ / ₄ " (222mm)

Parallel Installation
(Closer mounted on door on push side)



Same dimensions apply to Right Hand Doors.
Measurements B & C start from the edge of the door.

Closer size	A	FOR OPENING TO 120 °		FOR OPENING TO 180 °	
		B	C	B	C
2	7 ³ / ₈ " (187mm)	8 ³ / ₄ " (222mm)	9 ¹ / ₁₆ " (230mm)	7 ³ / ₈ " (187mm)	7 ¹¹ / ₁₆ " (195mm)
3	8 ³ / ₁₆ " (208mm)	8 ³ / ₈ " (213mm)	9 ¹ / ₁₆ " (230mm)	7" (178mm)	7 ¹¹ / ₁₆ " (195mm)
4&5	9 ¹ / ₁₆ " (230mm)	7 ¹⁵ / ₁₆ " (202mm)	9 ¹ / ₁₆ " (230mm)	6 ⁹ / ₁₆ " (167mm)	7 ¹¹ / ₁₆ " (195mm)

Finished color Abbreviations : AL (Aluminium) 、 DU (Dark Bronze) 、 BZ (Gold)

Three years warranty from delivery.