

## **FEATURES**

- @ Suitable for left hand, right hand, single and double action doors.
- @ No hold and 90  $^{\circ}\,$  hold open options. 105  $^{\circ}\,$  hold open available on special order.
- @ Medium strength spring for 120kgs doors up to 1200mm wide. Light spring for 120kgs doors up to 914mm wide
- @ Two independent valve control the closing and latching speeds.
- @ The closing action starts with the door fully open and ends at 15 ° from the closed position.
- @ Thus allowing the door to close at the desired speed.
- @ Changeable spindle insert available to suit field conditions.

## **Technical Data**

	Medium	Light
prox.	28	18
941mm		Yes
1200mm	Yes	
& double	Yes	Yes
peed variable	Yes	Yes
al	Yes	Yes
90°	Option	Option
105°	Option	Option
	120kgs	
	941mm 1200mm & double peed variable al	941mm  1200mm Yes & double Yes peed variable Yes al Yes 90 ° Option 105 ° Option

Length X Width X Height 283 X 131 X50 or 65

## **Door Control**

Two independent valve control the closing and latching speeds.

The closing action starts with the door fully open and ends at 15 from the closed position.


At this point the latching valve takes over, thus allowing the door to close at the desired speed.


#### **Back-Check**

The integral mechanical Back-Check helps to prevents damage to the door and wall in the event of the door being opened with excessive force.

## **Hold-Open**


With the Hold-Open feature (optional extra), the door can be held at angles of either 90 °or 105 °







- 1.Closing speed Valve
- 2.Latching speed Valve

# Options and accessories



RCTRACTABLE TOP CENTRE





HENG KUOCO., LTD. — TAIWAN
KUNSHAN HENG KUO MACHINERY CO., LTD

TAIWAN PLANT : No 136, Ren De 5, Ta-Shi, Tao Yuan Hsien, Taiwan, R. O. C
TEL: 886-3-380-2101 FAX: 886-3-380-2123

KUN SHAN PLANT : No 388 Lu Cnen Road Kun Shan City China
TEL: 86-512-86186625 FAX: 86-512-57570392